

# 2024 PIPELINE EMERGENCY QUICK REFERENCE GUIDE - KENTUCKY

## EMERGENCY CONTACT LIST

| <b>Company Name</b>                                  | <b>Emergency Number</b> |
|--|-------------------------|
| Atmos Energy.....                                    | 1-866-322-8667          |
| Atmos Pipeline and Storage, LLC.....                 | 1-866-322-8667          |
| AXP Energy, Inc. ....                                | 1-606-664-3810          |
| BP Pipelines (North America), Inc.....               | 1-800-548-6482          |
| CenterPoint Energy.....                              | 1-800-666-3895          |
| City of Elizabethtown Natural Gas Department.....    | 1-270-765-6121          |
| CNX Resources Corporation - Virginia Operations..... | 1-800-498-8225          |
| Columbia Gas of Kentucky Inc.....                    | 1-800-432-9515          |
| CountryMark Pipeline.....                            | 1-812-838-8500          |
| or (Ext 8500) .....                                  | 1-800-832-5490          |
| Delta Natural Gas Company, Inc. ....                 | 1-800-432-0771          |
| Diversified Gas & Oil Corporation.....               | 1-877-711-1138          |
| Duke Energy .....                                    | 1-800-634-4300          |
| Energy Transfer Crude Oil.....                       | 1-800-753-5531          |
| Enterprise Products Operating LLC.....               | 1-888-883-6308          |
| GLE Management Services LLC.....                     | 1-888-853-4799          |
| Greylock Production, LLC.....                        | 1-800-323-1855          |
| Mid-Valley Pipeline.....                             | 1-800-753-5531          |
| Monument Chemical Kentucky LLC (Ext 0).....          | 1-270-422-2101          |
| MPLX.....  | 1-866-342-6914          |
| TC Energy Natural Gas.....                           | 1-800-447-8066          |
| TC Energy Columbia Gas Transmission.....             | 1-800-835-7191          |
| TC Energy Columbia Gulf Transmission.....            | 1-866-485-3427          |
| Tennessee Gas Pipeline - Kinder Morgan, Inc. ....    | 1-800-231-2800          |
| Texas Eastern Transmission (Enbridge).....           | 1-800-231-7794          |
| Texas Gas Transmission, LLC.....                     | 1-800-626-1948          |
| Trunkline Gas.....                                   | 1-800-225-3913          |
| Valero Terminating and Distribution Company.....     | 1-866-423-0898          |
| Vinland Energy Operations LLC.....                   | 1-888-551-6402          |

To learn more about your local pipeline operators, please visit [ky.pipeline-awareness.com](http://ky.pipeline-awareness.com)

**Note:** The above numbers are for emergency situations. Additional pipeline operators/companies may exist in your area. Visit the National Pipeline Mapping System at [www.npms.phmsa.dot.gov](http://www.npms.phmsa.dot.gov) for transmission companies not listed above.

| <b>One-Call System</b> | <b>Phone Number</b>   |
|------------------------|-----------------------|
| Kentucky811.....       | 1-800-752-6007 or 811 |

# 2024 PIPELINE EMERGENCY QUICK REFERENCE GUIDE - KENTUCKY

## INCIDENT RESPONSE

- Always approach from upwind/park vehicle a safe distance away/if vehicle stalls – DO NOT attempt to restart
- Gather information/establish incident command/identify command structure
- Initiate communications with pipeline/gas company representative ASAP
- Control/deny entry: vehicle, boat, train, aircraft, foot traffic, media – refer all media questions to pipeline/gas representatives

## RISK CONSIDERATIONS

- Type/volume/pressure/location/geography of product
- Environmental factors – wind, fog, temperature, humidity
- Sight, sound, smell – indicators vary depending on product
- Black, dark brown or clear liquids/dirt blowing into air/peculiar odors/dead insects around gas line/dead vegetation
- Rainbow sheen on the water/mud or water bubbling up/frozen area on ground/frozen area around gas meter
- Other utility emergencies

## PIPELINE MARKERS

The U.S. Department of Transportation (DOT) requires the use of signs to indicate the location of underground pipelines. Markers like these are located on road, railroad, and navigable waterway crossings. Markers are also posted along the pipeline right-of-way. Markers may not be located directly over the pipeline it marks.

### The markers display:

- The product transported
- The name of the pipeline operator
- The operator's emergency number



## PRODUCT HAZARDS AND CHARACTERISTICS

### Petroleum (flow rate can be hundreds of thousands of gallons per hour) **TYPE 1**

- Flammable range may be found anywhere within the hot zone
- H2S can be a by-product of crude oil

| Type 1 Products | Flash Point | Ignition Temperature |
|-----------------|-------------|----------------------|
| Gasoline        | - 45 °F     | 600 °F               |
| Jet Fuel        | 100 °F      | 410 °F               |
| Kerosene        | 120 °F      | 425 °F               |
| Diesel Fuel     | 155 °F      | varies               |
| Crude Oil       | 25 °F       | varies               |

### Natural Gas (flow rate can be hundreds of thousands of cubic feet per hour) **TYPE 2**

- Flammable range may be found anywhere within the hot zone between 4% and 15%
- Rises and dissipates relatively quickly
- H2S can be a by-product of natural gas – PPM = PARTS PER MILLION
  - 0.02 PPM Odor threshold
  - 10.0 PPM Eye irritation
  - 100 PPM Headache, dizziness, coughing, vomiting
  - 200-300 PPM Respiratory inflammation within 1 hour of exposure
  - 500-700 PPM Loss of consciousness/possible death in 30-60 min.
  - 700-900 PPM Rapid loss of consciousness; death possible
  - Over 1000 PPM Unconsciousness in seconds; death in minutes

- Incomplete combustion of natural gas may release carbon monoxide
- Storage facilities may be present around populated areas/ can be depleted production facilities or underground caverns
- Gas travel may be outside the containment vessel along the natural space between the pipe and soil
- Lower/Upper Explosive Limit depends on characteristics of gas (SDS)

### Propane, Butane and Other Similar Products - **TYPE 3** (\*e.g. Carbon Dioxide / Anhydrous Ammonia)

- Flammable range may be found anywhere within the hot zone
- Products cool rapidly to sub-zero temperatures once outside the containment vessel
- Vapor clouds may be white or clear

| Type 3 Products   | Flash Point | Ignition Temperature |
|-------------------|-------------|----------------------|
| Propane           | - 150 °F    | 920-1120 °F          |
| Butane            | - 60 °F     | 725-850 °F           |
| Anhydrous Ammonia | - 51 °F     | 1204-1560 °F         |

- \* Caustic - Can freeze/burn skin
- \* Expands Rapidly
- \* Liquid to a fog gas state!

